



Unit: Millimeter (Inch)

	A	B	C	D
Positions	±0.25 (0.010)	±0.13 (0.005)	±0.38 (0.015)	±0.25 (0.010)
09	16.92 0.666	24.99 0.984	30.81 1.213	16.33 0.643
15	25.25 0.994	33.32 1.132	39.14 1.541	24.66 0.971
19	30.60 1.205	38.86 1.530	44.85 1.766	30.07 1.184
23	36.00 1.147	44.28 1.743	50.27 1.979	35.54 1.399
25	38.96 1.534	47.04 1.852	53.04 2.088	38.38 1.511
37	55.42 2.182	63.50 2.500	69.32 2.729	54.84 2.159

MOUNTING OPTION

CODE 1
HEX LOCKING SCREW
WITH BOARD LOCK



SPECIFICATIONS

Shell: Steel, Tin-plated
 Insulator :PBT+30% glass fiber , UL 94V-0
 Contact : Brass or Phosphor bronze
 Current rating (Max) : 5 amp AC / DC
 Withstanding voltage : 1000 VAC
 Insulation resistance (Min.):1000M Ω
 Contact resistance (Max):30M Ω
 Operating temperature : -55°C~+105°C

PROJ	SCALE : F DO NOT SCALE DWG	MOLD NO	3223
APP		MODEL	FILE NO
CHK	CCJ	92.07.05	CODE1
DGN	AMY	92.07.05	REV. X1
DRW	SHIEH	92.07.05	SIZE A4
		UNIT	SHT 1 OF 1
		MM	