



PCB LAYOUT

SPECIFICATIONS

Voltage Rating: 100V AC/DC
 Current Rating: 2A AC/DC
 Withstanding Voltage: 800V AC/minute
 Insulation Resistance: 1,000MΩ min.
 Temperature Range: -25° C - +85° C
 Contact Resistance: 20mΩ max

WAFER

Poles: 2-16
 Material: Nylon 66, UL94V-2
 Contact: Brass, Tin plated

NO	DIMENSION	
	A	B
02	2.00	6.00
03	4.00	8.00
04	6.00	10.00
05	8.00	12.00
06	10.00	14.00
07	12.00	16.00
08	14.00	18.00
09	16.00	20.00
10	18.00	22.00
11	20.00	24.00
12	22.00	26.00
13	24.00	28.00
14	26.00	30.00
15	28.00	32.00
16	30.00	34.00



PART NO. BSG-LPH-SXX

DRAWING NO.

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	SCALE
					~ 10	±0.15	DESIGN
				20 ~ 30	±0.30	CHECK	SIZE A4
				30 ~	±0.50	APPROVE	SHEET 1/1
				Angle	± 2'		PROJ. \blacktriangleleft
				DIM	TOL		

PART NO. BSG-LPH-SXX

DRAWING NO.